Embedded OS NVR- 4 Channel





- Powerful & Compact 1U 4-Ch NVR
- •Up to 4x 960p Video Channels
- Storage Capacity up to 4TB
- •No Extra Channel License Require
- Free Client and Mobile Clients apps

720P





Operating System Embedded LINUX 4x 960P ch 4x 1080P ch 4x 1080P ch 2x 1080P ch+2x 720P ch Playback 960P – 4 Ch 1080P – 1 Ch Support manual , auto, dynamic detection, alarm trigger record mode Backup Media USB Operation USB keyboard & mouse Storage Media Local HDD, network Audio Input 4ch network audio input Video Output VGA, HDMI, Analogue Audio Output 1ch BNC output Network 1 RJ45,100M lan port (optional) RS485 Port Full duplex standard 485 port (optional) USB Port 3 USB 2.0 ports Hard Drive 1x SATA Port, Max 4TB Mobile Apps iOS & Android Power Supply 12VDC, 3.5A Working Temperature -10°C +55°C Working Humidity 10%-90% Dimension Equipment: 260mm×220mm×43mm, Weight N.W.: 1.5Kg (no HDD)	Technical Details	Model: PE-NVR-4
Recording Channel Resolution 4x 1080P ch 2x 1080P ch+2x 720P ch 960P – 4 Ch 1080P – 1 Ch Recording Mode Support manual , auto, dynamic detection, alarm trigger record mode Backup Media USB Operation USB keyboard & mouse Storage Media Local HDD, network Audio Input Video Output VGA, HDMI, Analogue Audio Output Network 1 RJ45,100M lan port (optional) RS485 Port Full duplex standard 485 port (optional) USB Port 3 USB 2.0 ports Hard Drive 1x SATA Port, Max 4TB Mobile Apps iOS & Android Power Supply 12VDC, 3.5A Working Temperature -10°C~+55°C Working Humidity 10%-90% Dimension Equipment: 260mm×220mm×43mm,	Operating System	Embedded LINUX
Playback Recording Mode Support manual , auto, dynamic detection, alarm trigger record mode Backup Media USB Operation USB keyboard & mouse Storage Media Local HDD, network Audio Input Video Output VGA, HDMI, Analogue Audio Output 1ch BNC output Network 1 RJ45,100M lan port (optional) RS485 Port Full duplex standard 485 port (optional) USB Port 3 USB 2.0 ports Hard Drive 1x SATA Port, Max 4TB Mobile Apps iOS & Android Power Supply 12VDC, 3.5A Working Temperature -10°C~+55°C Working Humidity Dimension Equipment: 260mm×220mm×43mm,	Recording Channel Resolution	4x 1080P ch
Backup Media USB Operation USB keyboard & mouse Storage Media Local HDD, network Audio Input Video Output VGA, HDMI, Analogue Audio Output 1ch BNC output Network 1 RJ45,100M lan port (optional) RS485 Port Full duplex standard 485 port (optional) USB Port 3 USB 2.0 ports Hard Drive 1x SATA Port, Max 4TB Mobile Apps iOS & Android Power Supply 12VDC, 3.5A Working Temperature -10°C~+55°C Working Humidity 10%-90% Dimension Equipment: 260mm×220mm×43mm,	Playback	
Operation Storage Media Local HDD, network Audio Input Video Output VGA, HDMI, Analogue Audio Output Network 1 RJ45,100M lan port (optional) RS485 Port Full duplex standard 485 port (optional) USB Port 3 USB 2.0 ports Hard Drive 1x SATA Port, Max 4TB Mobile Apps iOS & Android Power Supply 12VDC, 3.5A Working Temperature -10°C~+55°C Working Humidity Dimension USB keyboard & mouse Local HDD, network 4ch network Audio Input VGA, HDMI, Analogue 1ch BNC output 1 RJ45,100M lan port (optional) 1 RS485 port (optional) 2 USB 2.0 ports 1 x SATA Port, Max 4TB 1 x SATA Port, Max	Recording Mode	Support manual , auto, dynamic detection, alarm trigger record mode
Storage Media Local HDD, network Audio Input 4ch network audio input Video Output VGA, HDMI, Analogue Audio Output 1ch BNC output Network 1 RJ45,100M lan port (optional) RS485 Port Full duplex standard 485 port (optional) USB Port 3 USB 2.0 ports Hard Drive 1x SATA Port, Max 4TB Mobile Apps iOS & Android Power Supply 12VDC, 3.5A Working Temperature -10°C → +55°C Working Humidity 10%-90% Dimension Equipment: 260mm×220mm×43mm,	Backup Media	USB
Audio Input Video Output VGA, HDMI, Analogue Audio Output 1ch BNC output Network 1 RJ45,100M lan port (optional) RS485 Port Full duplex standard 485 port (optional) USB Port 3 USB 2.0 ports Hard Drive 1x SATA Port, Max 4TB Mobile Apps iOS & Android Power Supply 12VDC, 3.5A Working Temperature -10°~+55°C Working Humidity 10%-90% Dimension 4ch network audio input VGA, HDMI, Analogue 1ch BNC output 1 RJ45,100M lan port (optional) 1 RJ45,100M lan port (optional) 1 RS485 port (optional) 1 USB 2.0 ports 1 x SATA Port, Max 4TB 1 x x SATA Port, Max 4TB 1 x x x x x x x x x x x x x x x x x x	Operation	USB keyboard & mouse
Video Output Audio Output 1ch BNC output Network 1 RJ45,100M lan port (optional) RS485 Port Full duplex standard 485 port (optional) USB Port 3 USB 2.0 ports Hard Drive 1x SATA Port, Max 4TB Mobile Apps iOS & Android Power Supply 12VDC, 3.5A Working Temperature -10°C~+55°C Working Humidity 10%-90% Dimension Equipment: 260mm×220mm×43mm,	Storage Media	Local HDD, network
Audio Output Network 1 RJ45,100M lan port (optional) RS485 Port Full duplex standard 485 port (optional) USB Port 3 USB 2.0 ports Hard Drive 1x SATA Port, Max 4TB Mobile Apps iOS & Android Power Supply 12VDC, 3.5A Working Temperature -10°C~+55°C Working Humidity 10%-90% Equipment: 260mm×220mm×43mm,	Audio Input	4ch network audio input
Network 1 RJ45,100M lan port (optional) RS485 Port Full duplex standard 485 port (optional) USB Port 3 USB 2.0 ports Hard Drive 1x SATA Port, Max 4TB Mobile Apps iOS & Android Power Supply 12VDC, 3.5A Working Temperature -10°C~+55°C Working Humidity 10%-90% Dimension Equipment: 260mm×220mm×43mm,	Video Output	VGA, HDMI, Analogue
RS485 Port Full duplex standard 485 port (optional) USB Port 3 USB 2.0 ports Hard Drive 1x SATA Port, Max 4TB Mobile Apps iOS & Android Power Supply 12VDC, 3.5A Working Temperature -10°C~+55°C Working Humidity 10%-90% Equipment: 260mm×220mm×43mm,	Audio Output	1ch BNC output
USB Port 3 USB 2.0 ports Hard Drive 1x SATA Port, Max 4TB Mobile Apps iOS & Android Power Supply 12VDC, 3.5A Working Temperature -10°C~+55°C Working Humidity 10%-90% Dimension Equipment: 260mm×220mm×43mm,	Network	1 RJ45,100M lan port (optional)
Hard Drive 1x SATA Port, Max 4TB Mobile Apps iOS & Android Power Supply 12VDC, 3.5A Working Temperature -10℃∼+55℃ Working Humidity 10%-90% Dimension Equipment: 260mm×220mm×43mm,	RS485 Port	Full duplex standard 485 port (optional)
Mobile AppsiOS & AndroidPower Supply12VDC, 3.5AWorking Temperature-10°C∼+55°CWorking Humidity10%-90%DimensionEquipment: 260mm×220mm×43mm,	USB Port	3 USB 2.0 ports
Power Supply 12VDC, 3.5A Working Temperature $-10^{\circ}\text{C} \sim +55^{\circ}\text{C}$ Working Humidity 10%-90% Equipment: 260mm×220mm×43mm,	Hard Drive	1x SATA Port, Max 4TB
Working Temperature $-10^{\circ}\text{C} \sim +55^{\circ}\text{C}$ Working Humidity 10% -90% Dimension Equipment: 260mm×220mm×43mm,	Mobile Apps	iOS & Android
Working Humidity 10%-90% Dimension Equipment: 260mm×220mm×43mm,	Power Supply	12VDC, 3.5A
Dimension Equipment: 260mm×220mm×43mm,	Working Temperature	-10℃~+55℃
The state of the s	Working Humidity	10%-90%
Weight N.W.: 1.5Kg (no HDD)	Dimension	Equipment: 260mm×220mm×43mm,
	Weight	N.W.: 1.5Kg (no HDD)





Apps Available on





