






- Mini Ceiling Flush Mount Dome
- Vandal Resistant
- Up to 3 Mega Pixel
- Synchronize Audio Input
- True Day/Night, Wide Dynamic



Technical Details	Resolution		
	1.0MP	1.3MP	3.0MP
Video Compression	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG
Image Sensor	1/4", 1.0 MP, CMOS	1/3", 1.3MP, CMOS	1/3" CMOS, 3.1MP,
Max Video Resolution	1280Hx800V	1280H x 960V	2048Hx1536V
Max Frame Rate	1280x720 -30fps	1280x960 – 25fps 1280x720 – 30fps	2048x1536 -15fps 1920x1080 – 30fps
Lens	f=2.8mm or f=3.6mm		
Day/Night	IR Cut Control		
Min. illumination	0.05Lux; (0 Lux with IR)		
Min. illumination Response	3.30 V/lux-sec (550nm)	5.48 V/lux-sec (550nm)	1.90 V/lux-sec (550nm)
Wide Dynamic Range	100db	110db	100db
Video Output	NTSC or PAL Complex video signal		
Video Compression Type	Video Stream / Complex Video Stream		
Compressed Video Output rate	32Kbps - 8Mbps		
Audio Input	MIC IN		
Audio Output	Linear output (LINEOUT · 600Ω, Optional)		
Audio Compression Standard	G.711 u/A, AAC		
Audio Compression Rate	16-96kbps · support8-16KHz		
Network Connection	RJ45 10M/100M Ethernet		
Power	PoE, IEEE 802.3af		
Operation Temperature	-20°C – 50°C		
Operation Humidity	10–90%(non-condensing)		
Dimension	99mm diameter, 107mmH		
Opening	82mm diameter		
Weight	~200g		



Options	Available Model		
	1.0MP	1.3MP	3.0MP
2.8mm Lens, White	PQ10P1-28	PQ13P1-28	PQ30P1-28
2.8mm Lens, Black	PQ10P2-28	PQ13P2-28	PQ30P2-28
3.6mm Lens, White	PQ10P1-36	PQ13P1-36	PQ30P1-36
3.6mm Lens, Black	PQ10P2-36	PQ13P2-36	PQ30P2-36

Quick Instalation Design

